

Pendock, Halesfield 19, Telford, Shropshire, TF7 4QT.  
 T 01952 580590  
 F 01952 587805  
 E sales@pendock.co.uk  
 W www.pendock.co.uk

**THIS DRAWING MUST NOT BE SCALED**

© COPYRIGHT TP MANUFACTURING

THIS DRAWING MUST BE REVIEWED IN CONJUNCTION WITH ANY SUPPORTING QUOTATIONS REFERENCED.

THE DESIGN DETAILED IN THIS DRAWING FORMS PART OF A PROPOSED SOLUTION.

ALL QUANTITIES AND MEASUREMENTS MUST BE CHECKED IN CONJUNCTION WITH SUPPORTING QUOTATION AGAINST CLIENTS REQUIREMENTS. SPECIFIC CONSIDERATION SHOULD BE GIVEN TO DIMENSIONAL ACCURACY (INCLUDING INT. CLEARANCE).

PENDOCK SHALL NOT BE LIABLE FOR ANY CLAIM ARISING OUT OF THE USE OF THIS DESIGN IN A SCHEME NOT APPROVED IN WRITING BY PENDOCK.

THIS DRAWING MUST NOT BE LENT OR COPIED, AND THE DESIGN MUST NOT BE COPIED. COPYRIGHT AND DESIGN RIGHT IN THIS DRAWING RESTS WITH PENDOCK.


THE CUSTOMER OR ITS CONTRACTOR OR AGENT IS RESPONSIBLE FOR VERIFYING THE ACCURACY AND SUITABILITY OF THE DESIGN IN THIS DRAWING.

PENDOCK STANDARD TERMS AND CONDITIONS, DETAILED ON SUPPORTING QUOTATIONS APPLY.

## NOTES


REV	DATE		BY	APP
-----	------	--	----	-----

GENERAL INFORMATION  
 ALL DIMENSIONS IN MM  
 UNLESS OTHERWISE STATED



DATE	DRAWN	CHECKED	APPROVED
27.8.14	SL		

CLIENT/PROJECT

**Metal Columns  
Circular**


PROJECT DETAILS

**Pendock Column  
Casings**


SCALE	nts	SHEET	3 OF 4	A3
DWG No.				REV

## Fitment Guide

Female column section  
 first fix  
 (Internal flange to flange size  
 smaller than male section)




Male Column Section  
 Fixed over female section  
 (Internal flange to flange size  
 greater than Female section)



Female casing fixed to mullion  
 (fixings to be countersunk to allow  
 over fitment of Male casing)

Male casing located over female  
 flange and fixed into mullion.  
 (Avoid the same drilling position  
 as the Female section)

Feature Joint  
 (feature joint is not a compression  
 fit and will require bonding into  
 position a small self tapping screw  
 can be used at the head and base  
 to aid securing)



Using the Aluminium (or Timber) mullion as a spline offer the female enclosure (smaller internal dimension) so that the required amount of inner collar is revealed. Screw through the joint and into the mullion. Countersunk screws are required for this first section as the second section locates on top of the flange.

Offer the second half of the enclosure (male section) using a tourniquet to hold both halves into place, screwfix through joint into the aluminium mullion. Avoid the same drilling position as the female section

Insert feature joint cover strips to cover fixings and use a suitable mastic to hold into place. The feature joint is not a compression fit and will require mastic, a small self tapping screw can be used at the head and base to aid securing.