



Specification:

Material thickness: 3mm Aluminium (2mm available for smaller sizes)
 Finish: Mill Finish, PPC (Polyester Powder Coated)
 Lengths available: 2500mm 3000mm 4000mm dependent on profile dimensions
 (profiles can be ordered to specific lengths)

Accessories:

Internal and external 90° corners available.
 Internal timber fixing battens available (38x25)
 Internal aluminium fixing angles available (sizes 25x25 to 50x50)
 Internal or external jointing straps available

Bespoke designs and profiles available on request to suit specific specifications and finishes.

Dimensions over 300mm/600mm also available on request

Notes:

When specifying dimensions of the CHM profile required the width of the profile must be greater than the depth of the profile.

Standard fitment profiles 'Butt' jointed together.

Welded external/internal jointing flange available.

Mechanical tamper proof fixings/fasteners are recommended and should be sourced separately.

Earthing strips may be required (refer to project specification) and sourced separately

PENDOCK

Pendock Ltd.
 Halesfield 19, Telford, Shropshire, TF7 4QT.
 Tel: +44 (0) 1952 580590 Fax: +44 (0) 1952 587805
 E-mail: technical@pendock.co.uk
 Web: www.pendock.co.uk

THIS DRAWING MUST NOT BE SCALED

© COPYRIGHT TP MANUFACTURING LTD
 HALESFIELD 19, TELFORD, SHROPSHIRE TF7 4QT
 TEL: +44 (0) 1952 580590 FAX: +44 (0) 1952 587805
 email: sales@pendock.co.uk or technical@pendock.co.uk

CHM PROFILE

DRAWN BY	SCALE	DATE
SL	NTS	29/4/15