



### <u>Specification:</u>

Material thickness: 3mm Aluminium (2mm available for smaller sizes)

Finish: Mill Finish, PPC (Polyester Powder Coated)

Lengths available: 2500mm 3000mm 4000mm dependent on profile dimensions

(profiles can be ordered to specific lengths)

## Accessories:

Internal and external 90° corners available.

Internal timber fixing battens available (38x25)

Internal aluminiumn fixing angles available (sizes 25x25 to 50x50)

Internal or external jointing straps available

Bespoke designs and profiles available on request to suit specific specifications and finishes.

Dimensions over 500mm also available on request.

#### Notes:

Standard fitment profiles 'Butt' jointed together.

Welded external/internal jointing flange available.

Mechanical tamper proof fixings/fasteners are recommended and should be sourced seperately.

Earthing strips may be required (refer to project specification) and sourced seperately

# PENDOCK

Pendock Ltd. Halesfield 19, Telford, Shropshire, TF7 4QT.

Tel: +44 (0) 1952 580590 Fax: +44 (0) 1952 587805
E-mail: technical@pendock.co.uk
Web: www.pendock.co.uk

#### THIS DRAWING MUST NOT BE SCALED

© COPYRIGHT TP MANUFACTURING LTD HALESFIELD 19, TELFORD, SHROPSHIRE TF7 4QT EL: +44 (0) 1952 580590 FAX: +44 (0) 1952 587805 email: sales@pendock.co.uk or technica@pendock.co.uk

MXM PROFILE

DRAWN BY SCALE DATE SL NTS 29/4/15